# **Evidence of Performance**

Ageing behaviour of insulating glass units as per DIN EN 1279-3

Test Report 601 34743/3e



Client Holis Metal Industries LTD.

Industrial Zone Alon-Tavor

Afula, 18550

Israel

Insulating glass units - gas filled Product

Designation Exterior

V2W

dimensions  $(W \times H)$ 

500 mm x 500 mm

4 ESG / 29 / 4 ESG Configuration

Lower spacer profile:

Aluminum, 29 mm, company Lingemann

Head and vertical spacer profile:

Spacers

Sealants

External Polysulphide, PS 998 R, company H.B. Fuller

Aluminium, 29 mm, company Erbslöh

internal Polyisobutylene, PIB 969, company H.B. Fuller

Inner frame without moving shading device inserted in

cavity Special features

The insulating glass was tested following DIN EN 1279-3



Gas leakage rate

 $L_{e1} = 0.81 \% /a$ 

 $L_{e2} = 0.61 \% /a$ 

and fulfils the requirements of the ift-guideline VE-07/2

#### Basis

DIN EN 1279-3: 2003-05; Glass in building - Insulating glass units - Part 3: Long term test method and requirements for gas leakage rate and for gas concentration tolerances

ift-Guideline VE-07/2: 2005-8, Insulating glazing units with movable shading devices integrated in the interpane separation, chapter 4.2

#### Instructions for use

This test report serves to demonstrate the gas leakage rate and gas concentration tolerances of insulating glass

## Validity

The data and results given relate solely to the tested and described specimen.

The long term test does not imply any statement on characteristics regarding performance and quality.

### **Publishing notes**

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents applies.

The cover sheet can be used as abstract.

Contents

The test report comprises a total of 6 pages

- Object
- Procedure
- 3 Detailed results
- 4 Evaluation

Summary

ift Rosenheim 15 May 2008

Karin Lieb, Dipl.-Ing. (FH) Head of Testing Department

ift Centre Glass, Building Materials & Building **Physics** 

Irina Hausstetter, Dipl.-Ing. (FH) Test engineer

ift Centre Glass, Building Materials & Building **Physics** 

Dipl.-Ing. (FH) Ulrich Sieberath Dr. Jochen Peichl

Geschäftsführer